

ACCEPTABLE TYPICAL HOUSE CONNECTIONS

RCO SECTION 502.2.1 AND TABLE 301.5

2013

LEDGER LOCKS
SEE SECTION R502.2.1

FLASHING:
STUCCO / BRICK:
SEE SECTION R703.8

INSTALL LAG SCREWS
THAT PENETRATE 1-1/2"
MINIMUM INTO RIM JOIST
OR WALL STUDS. (3/8"
LAGS EVERY 16" OR
EQUIVALENT) STAGGERED

JOIST HANGER

LEDGER BOARD TO BE
SAME SIZE AS JOISTS.

PROVIDE BLOCKING FOR
JOIST INSTALLATIONS

INSTALL LAG SCREWS
THAT PENETRATE 1-1/2"
MINIMUM INTO RIM JOIST
OR WALL STUDS. (3/8"
LAGS EVERY 16" OR
EQUIVALENT) STAGGERED

2X2 LEDGER BOARD
FASTENED WITH 16d
NAILS. (3 NAILS FOR
EACH JOIST TO BE
SUPPORTED)

LEDGER BOARD TO BE
LARGER THAN JOISTS.

PROVIDE BLOCKING FOR
JOIST INSTALLATIONS

LEDGER DETAIL

ALTERNATE LEDGER